

SHOWER TRAY, SHOWER TRAYS (ACRYLIC, QUARYL), SHOWER TRAYS SQUARO INFINITY

PRODUCT INFORMATION



Model	UDQ1590SQI2LV
Width	900 mm
Height	40 mm
Depth	15 mm
Length	1500 mm
Weight	38 kg
Description	<p>corner installation, left against the wall</p> <p>Technical information:: Cut shower tray (side unprocessed)., Drainage capacity: 48 l/min, The installation height of the shower tray can be reduced by 30 mm if the Viega outlet fitting art. no. 634 100 is used. Please note: this outlet fitting does not conform to EN 274., All shower trays are classified as anti-slip class C (in accordance with DIN51097), Surface-mounted models can be fitted in corners on the left against the wall, in a niche or flush-fit with the floor., Quarryl shower trays can be cut to size on site according to the installation instructions; detailed video at pro.villeroy-boch.com/squaroinfinity or QR code on this page.</p> <p>These shower trays are cut along the short side.</p> <p>Outlet cover in matching matt colour with chrome-plated strip., The extra charge for cutting already in the total price!</p> <p>Not included in scope of delivery:: All shower trays are supplied without support/base., With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.</p> <p>With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.</p> <p>Diameter: 90 mm</p>
Material	Quaryl®

Specification texts

Squaro Infinity; Shower tray; Size: 1500 x 900 x 40 mm; Quarryl®; corner installation, left against the wall; Outlet cover in matching matt colour with chrome-plated strip., **The extra charge for cutting already in the total price!**; Not included in scope of delivery.: All shower trays are supplied without support/base., With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.; Diameter: 90 mm; With cut shower trays, we recommend the use of a composite seal in accordance with ETAG 022 on the floor structure below the shower tray in order to prevent any moisture from penetrating the floor structure.; Technical information.: Cut shower tray (side unprocessed)., Drainage capacity: 48 l/min, The installation height of the shower tray can be reduced by 30 mm if the Viega outlet fitting art. no. 634 100 is used. Please note: this outlet fitting does not conform to EN 274., All shower trays are classified as anti-slip class C (in accordance with DIN51097), **Surface-mounted models can be fitted in corners on the left against the wall, in a niche or flush-fit with the floor., Quarryl shower trays can be cut to size on site according to the installation instructions; detailed video at pro.villeroy-boch.com/squaroinfinity or QR code on this page.**; These shower trays are cut along the short side.

COLOURS

Anthracite	UDQ1590SQI2LV-1S	4051202456467
Crème	UDQ1590SQI2LV-2S	4051202457679
Grey	UDQ1590SQI2LV-3S	4051202458881
Brown	UDQ1590SQI2LV-4S	4051202460099
Stone White	UDQ1590SQI2LV-RW	4051202852054

UDQ1590SQI2LV

SQUARO INFINITY
UDQ1590SQI2L

Villeret & Biech
1712
 • This drawing is for information only.
 • It is not a contract document.
 • All dimensions are in millimeters.
 • Product for drawing will not be accepted.

